



GRAND CLEAR 1K WOOD FLOOR FINISH



SPECIFICATIONS

VOC.....	<275 g/L
Solids.....	30 - 32%
Flash Point.....	>212° F
Solvents.....	Water/Glycol Ether
Shelf Life.....	1 Year Unopened
Coverage.....	450 - 500 sq. ft/gal
Color.....	Clear

FEATURES

- Crystal Clear Non-Yellowing
- Advanced Resin Technology
- Easy to Apply
- Water Cleanup
- Scuff Resistant

CLEAR FLOOR FINISH FOR ALL HARDWOODS

Absco™ Grand Clear 1K Wood Floor Finish is the newest generation of water cleanup wood floor finish for professionals. Its crystal clear non-yellowing formula combines Advanced Resin Technology to offer durability and scuff resistance. And it's easy to apply with water cleanup. The Professional's Choice for over 40 years, Absco™ is manufactured from the highest quality resins. For interior use only.

SURFACE PREPARATION: New Wood or Newly Sanded Floors: Prepare the floor according to the NWA or NOFMA accepted manner. Make several passes with the sandpaper, increasing the paper fineness with each pass. The final pass before application of Absco Grand Clear 1K should be with a #100 grit screen disc or sandpaper. Remove dust completely by sweeping, vacuuming and wiping the floor with a lightly dampened lint free cloth. The floor, product and room temperature should be at least 65 degrees F.

SURFACE PREPARATION: Previously Finished Floors: Remove old finish in poor condition completely. All wax, grease, soaps and dirt must be removed thoroughly. For floors in good condition, screen the floor #120 to #150 Screen disc, or #180 grit sandpaper. Remove dust completely by sweeping, vacuuming and wiping the floor with a lightly dampened lint free cloth.

AVAILABLE IN: HIGH GLOSS, SEMI-GLOSS, SATIN and MATTE FINISHES in one- and five-gallon containers only.